



RIKA Innovative Ofentechnik GmbH
 A-4563 Micheldorf, Müllerviertel 20
 21
 0080-CPR-07.2013

EN 14785:2006

Notified Body Nr.: 1746

Intended use: Space heating in residential buildings without possible supply of hot water

Name: CONNECT PELLET F22 / F38

space heating appliances fired by wood pellets – system 3
 (height x width x depth = 1210 mm x 660/845 mm x 420 mm)

Fire safety	pass
Distance to combustibles	rear 70 mm sides 100 mm ceiling 800 mm floor 0 mm
Emission of combustion products	pass
- CO emission – wood pellets	0,003% / nominal heat output
Release of dangerous substances	NPD
Surface temperature	pass
Electrical safety	pass
Cleanability	pass
Maximum operating pressure	not applicable
Flue gas outlet temperature at nominal heat output	170,4 °C
Mechanical resistance (to carry a chimney)	NPD
Thermal output / Energy efficiency	pass
– nominal heat output	8 kW
– water heat output	not applicable
– space heat output	8 kW
– efficiency	91,5 %
Durability	pass
recommended fuel type	wood pellets
Shared flue system	yes
Emission (addition)	
- PM wood pellets	10 mg/m ³
- OGC wood pellets	3 mg/m ³
- NO _x wood pellets	108 mg/m ³
Emission (requirements according AT 15A)	
- CO wood pellets	22 mg/MJ
- PM wood pellets	6 mg/MJ
- OGC wood pellets	3 mg/MJ
- NO _x wood pellets	69 mg/MJ
Please read manufacturer's operating instructions carefully before installing and using the appliance!	

Signed on behalf of the manufacturer


 Innovative Ofentechnik GmbH
 A-4563 Micheldorf, Müllerviertel 20
 Tel.: +43(0)7582/686-41, Fax DW: -43
 www.rika.at

Andreas Bloderer / product manager

Name and function

Micheldorf, 09.09.2021

Place and date of issue