



RIKA Innovative Ofentechnik GmbH
AT-4563 Micheldorf, Müllerviertel GmbH
19
76-CPR-07.2013

| | | |
|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|----------------|
| EN14785:2006 | | |
| Notified Body: | 1746 | |
| Intended use: | Space heating in residential buildings without possible supply of hot water | |
| Name: | PRIMO 6 kW / PRIMO RAO 6 kW / PRIMO PGI 6 kW / PRIMO MA 6 kW | |
| Description: | space heating appliances fired by wood pellets - system 3 | |
| Height | 1007 mm | |
| Width | 496 mm | |
| Depth | 520 mm | |
| Fire safety | pass | |
| Safety distance to combustible material | rear | 100 mm |
| | sides | 100 mm |
| | top | 500 mm |
| | front | 800 mm |
| | floor | 12 mm |
| Emission of combustion products | pass | |
| CO-Emission at nominal heat output | < 0,02 % | |
| CO-Emission at nominal heat output | < 0,25 g/Nm ³ | |
| Release of dangerous substances | NPD | |
| Surface temperature | pass | |
| Electrical safety | pass | |
| Cleanability | pass | |
| Durability | pass | |
| Mechanical resistance (to carry chimney) | NPD | |
| Maximum operating pressure | not applicable | |
| Flue gas temperature at the measuring section at nominal heat output | 125,2 °C | |
| Flue gas temperature outlet at nominal heat output | 150,2 °C | |
| Thermal output | pass | |
| Nominal- / part load heat output | 6 kW | 2,5 kW |
| Nominal- / part load space heat output | 6 kW | 2,5 kW |
| Nominal- / part load water heat get output folder path | not applicable | not applicable |
| Efficiency | pass | |
| Nominal- / part load Efficiency | 91,7 % | 94,3 % |
| recommended fuel type | wood pellets (ISO 17225-2) | |
| Suitability for installation to a shared flue system | yes | |
| Emission (addition) | | |
| CO wood pellets | g/Nm ³ | < 0,25 |
| PM wood pellets | g/Nm ³ | < 0,02 |
| OGC wood pellets | g/Nm ³ | < 0,06 |
| NO _x wood pellets | g/Nm ³ | < 0,20 |
| Emission (requirements according AT 15A) | | |
| CO wood pellets | mg/MJ | < 500 |
| PM wood pellets | mg/MJ | < 25 |
| OGC wood pellets | mg/MJ | < 30 |
| NO _x wood pellets | mg/MJ | < 100 |
| Pleas read manufacturer's operating instructions carefully before installing and using the appliance! | | |



Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel: +43 (0)7582/686-14, Fax DW: -43
www.rika.at

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 14.12.2021

Place and date of issue